



Applications

- > Programming and operating Videofied security systems.

Electrical Data

| | |
|---------------------------|----------------------------------|
| Power requirements | One battery |
| Battery type | Lithium 3.0V CR123 |
| Battery life | 4 years |
| Technology | WiseLink® |
| Radio type | Spread Spectrum Bidirectional RF |
| Operating frequency | 868/915 MHz |
| Transmission security | AES algorithm encryption |
| Supervision | polled signal every 8 minutes |
| Antenna | Integrated |
| Tamper detection | Wall and cover tampered |
| Operating temperature | 0°/+40°C (32°/104°F) |
| Shocks | IK07 |
| Protection | IP30 |
| Maximum relative humidity | 70%, non-condensing |
| Approvals | CE (SD200) / UL 268 (SD600) |

Physical Data

| | |
|----------|--------------------------|
| Material | ABS-ULV0 |
| Height | 55 mm |
| Diameter | 120 mm |
| Weight | 185g (without batteries) |

Features

- > Recording by push button under the cover.
- > Internal serial Nb, and bar code.
- > Opening, ripping off and normally closed input.
- > Built in 85 dB.
- > Optical detection of visible particles.
- > Efficiency : 55m².

Installation/Mounting

| | |
|---------------------|--------------------|
| Wall fixing | 2 screws |
| Positioning | By oblong holes |
| Front cover closing | By bottom screws |
| Mounting adjustment | No, pre positioned |



SD means SD600 for USA/Canada and SD200 for Europe and rest of the world.

EMEA SALES

23, avenue du Général Leclerc
92340 BOURG-LA-REINE
FRANCE

E-Mail : emeasales@rsivideotech.com

North American Headquarters

4455 White Bear Parkway, Suite 700
White Bear Lake, MN 55110
USA

E-Mail : usasales@rsivideotech.com

